

# BRYM3N50AF

Rev.A Jul.-2024

## 描述 / Descriptions

PDFN5×6A 塑封封装双 N 沟道场效应管。

Dual N-CHANNEL MOSFET in a PDFN5×6A Plastic Package .

## 特征 / Features

$V_{DS}(V)=500V$   $I_D=1.4A$

$R_{DS(ON)}@10V \leq 3.5\Omega$  (Typ. 2.8 $\Omega$ )

快速开关。Fast Switching.


无卤产品。HF Product.

## 用途 / Applications


该器件非常适合适配器和充电器的电源开关电路，集成快速恢复二极管。

These devices are well suited for power switch circuit of adaptor and charger, intergrate fast recovery diode.

## 内部等效电路 / Equivalent Circuit



## 引脚排列 / Pinning



## 印章代码 / Marking

见印章说明。

See Marking Instructions.

**极限参数 / Absolute Maximum Ratings(Ta=25°C)**

参数 Parameter	符号 Symbol	数值 Rating	单位 Unit
Drain-Source Voltage	$V_{DSS}$	500	V
Drain Current	$I_D(T_c=25^\circ\text{C})$	1.4	A
Drain Current - Pulsed	$I_{DM}$	4.3	A
Gate-Source Voltage	$V_{GS}$	$\pm 30$	V
Single Pulsed Avalanche Energy	$E_{AS}$	112.5	mJ
Avalanche Current	$I_{AS}$	4.5	A
Power Dissipation	$P_D(T_c=25^\circ\text{C})$	25	W
Operating and Storage Temperature Range	$T_J, T_{STG}$	-55 to 150	$^\circ\text{C}$
Junction to Case	$R_{\theta JC}$	8.3	$^\circ\text{C/W}$

**电性能参数 / Electrical Characteristics(Ta=25°C)**

参数 Parameter	符号 Symbol	测试条件 Test Conditions	最小值 Min	典型值 Typ	最大值 Max	单位 Unit
Drain-Source Breakdown Voltage	$BV_{DSS}$	$V_{GS}=0V$ $I_D=250\mu A$	500			V
Zero Gate Voltage Drain Current	$I_{DSS}$	$V_{DS}=500V$ $V_{GS}=0V$			1	$\mu A$
Gate-Body Leakage Current Forward	$I_{GSS}$	$V_{GS}=\pm 30V$ $V_{DS}=0V$			$\pm 100$	nA
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS}=V_{GS}$ $I_D=250\mu A$	2.0	3.0	4.0	V
Static Drain-Source On-Resistance	$R_{DS(on)}$	$V_{GS}=10V$ $I_D=1.5A$		2.8	3.5	$\Omega$
Drain-Source Diode Forward Voltage	$V_{SD}$	$V_{GS}=0V$ $I_S=3.0A$			1.4	V
Input Capacitance	$C_{iss}$	$V_{DS}=25V$ $V_{GS}=0V$ $f=1.0MHz$		220		pF
Output Capacitance	$C_{oss}$			130		
Reverse Transfer Capacitance	$C_{rss}$			5		
Total Gate Charge	$Q_G$	$V_{DS}=400V$ $I_D=3.0A$ $V_{GS}=10V$		12.5		nC
Gate-Source Charge	$Q_{GS}$			3.2		
Gate-Drain Charge	$Q_{GD}$			4.2		

## 电性能参数 / Electrical Characteristics(Ta=25°C)

参数 Parameter	符号 Symbol	测试条件 Test Conditions	最小值 Min	典型值 Typ	最大值 Max	单位 Unit
Turn-On Delay Time	$t_{d(on)}$	$V_{DD}=100V$ $I_D=3.0A$ $V_{GS}=10V$ $R_G=25\Omega$		5.2		ns
Turn-On Rise Time	$t_r$			20.3		
Turn-Off Delay Time	$t_{d(off)}$			45		
Turn-Off Fall Time	$t_f$			28		
Reverse Recovery Time	$t_{rr}$	$V_{GS}=0V$ $I_S=3.0A$ $di_F/dt=100 A/\mu s$		64		ns
Reverse Recovery Charge	$Q_{rr}$			0.8		$\mu C$

电参数曲线图 / Electrical Characteristic Curve




Fig 1: On-Region Characteristics




Figure 2: Transfer Characteristics




Figure 3: On-Resistance vs. Drain Current and Gate Voltage




Figure 4: On-Resistance vs. Junction Temperature




Figure 5: Break Down vs. Junction Temperature




Figure 6: Body-Diode Characteristics

## 电参数曲线图 / Electrical Characteristic Curve




Figure 7: Gate-Charge Characteristics




Figure 8: Capacitance Characteristics




Figure 9: Maximum Forward Biased Safe Operating Area





Figure 10: Normalized Maximum Transient Thermal Impedance

**外形尺寸图 / Package Dimensions**


PDFN5 X6A

Unit:mm



Rev.01 202209

**印章说明 / Marking Instructions**



说明：

BR： 为公司代码

3N50AF： 为型号代码

\*\*\*\*： 为生产批号代码，随生产批号变化

Note：

BR： Company Code

3N50AF： Product Type Code

\*\*\*\*: Lot No. Code, code change with Lot No

回流焊温度曲线图(无铅) / Temperature Profile for IR Reflow Soldering(Pb-Free)



说明：

- 1、预热温度 150~180°C，时间 60~90sec;
- 2、峰值温度 245±5°C，时间持续为 5±0.5sec;
- 3、焊接制程冷却速度为 2~10°C/sec.

Note:

- 1.Preheating:150~180°C, Time:60~90sec.
- 2.Peak Temp.:245±5°C, Duration:5±0.5sec.
3. Cooling Speed: 2~10°C/sec.

耐焊接热试验条件 / Resistance to Soldering Heat Test Conditions

温度：260±5°C

时间：10±1 sec.

Temp.:260±5°C

Time:10±1 sec

包装规格 / Packaging SPEC.

卷盘包装 / REEL

Package Type 封装形式	Units 包装数量					Dimension 包装尺寸 (unit: mm <sup>3</sup> )		
	Units/Reel 只/卷盘	Reels/Inner Box 卷盘/盒	Units/Inner Box 只/盒	Inner Boxes/Outer Box 盒/箱	Units/Outer Box 只/箱	Reel	Inner Box 盒	Outer Box 箱
PDFN5×6A	5,000	2	10,000	6	60,000	13"×12	360×360×50	380×335×366

使用说明 / Notices